



Submittal Data Sheet

Indoor Unit Model#: ACiQ-24FM-HH-MD

24K Ceiling & Floor Mount Air Handler (Multi-Zone Systems)

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:

Indoor Unit Product Code: 810175551296



INDOOR UNIT SPECIFICATIONS

Indoor Air Flow (Turbo/H/M/L/Si) (CFM)		735.8 / 706.3 / 606.3 / 453.2 / 376.7
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)		51.5 / 49.0 / 45.0 / 34.0 / 29.0
Dimension (W×D×H)	inch	42.05 x 26.57 x 9.25
	mm	1068.0 x 675.0 x 235.0
Package (W×D×H)	inch	45.08 x 29.72 x 12.52
	mm	1145 x 755 x 318
Net/Gross Weight	lbs	61.29 / 73.19
	kg	27.8 / 33.2

ELECTRICAL SPECIFICATIONS

Power Supply	208/230V, 60Hz, 1Ph
Connection Wiring	14#x4
Indoor Fan Motor RLA	1.0
Indoor Fan Motor W	90
RLA: Rated load amps (A)	W: Fan motor rated output (W)

REFRIGERANT PIPING SPECIFICATIONS


Liquid Size	9.52mm (3/8in)
Gas Size	15.9mm (5/8in)
Connection Method	Flared
Refrigerant	R454B

Features

- 2 Style Installation
- 3D Airflow
- Refrigerant leakage detection sensor
- Humidity sensor
- "88" display tube
- 1~100% fan speed setting
- WiFi capability: through WiFi dongle or wired controller with built-in WiFi
- OTA (by using WiFi dongle)
- 2-pin connector (HA/HB) for programmable wired controller
- Multiple control options available:
 - Two way communication wired controller: 120N (X6)
 - Two way communication wired controller with built-in WiFi: 120N (X6W)
 - Infrared wired controller: 120L
 - Wireless remote controller
 - Third-Party 24V Thermostat*

*24V interface is required.

Indoor Unit Dimensions



Model	A	B	C	D
18K/24K	42in(1068mm)	26-1/2in(675mm)	9-1/4in(235mm)	38-3/4in(983mm)
36K/48K/60K	65in(1650mm)	26-1/2in(675mm)	9-1/4in(235mm)	61-5/8in(1565mm)

Indoor Unit Installation Instructions

