

Specifications

PFXE100CP KERNA COMMERCIAL SENSOR LAVATORY FAUCET



Product Features

- Touch-free deck-mounted electronic faucet
- Cold or premixed water
- Dual power (110V plug with 9V battery backup or 9V battery only) with battery box and transformer included (batteries not included)
- Chrome-plated body
- Activated by a concealed sensor in the spout
- Filter included
- Low battery indicator
- Adjustable sensor settings: Sensor range, security time, delay in, delay out, on-off, factory reset. Remote control required - sold separately. Factory settings will suffice for most applications and users. In the rare case that custom settings are desired, the optional remote control indicated below is required
- The faucet is automatically activated when users place their hands in the sensor range and shuts off when the user's hands are removed
- Vandal-resistant aerator
- Power supply options: 9V battery or 9V transformer
- Operating pressure: 0.5-8.0 bar/7.0-116.0 psi
- Water supply: Cold or premixed water
- Water saving options: 0.5 gpm (default), 0.35 gpm (OBPF508510067)
- Water temperature: 158°F maximum (70°C)
- Security time: Auto shutoff after 90 seconds, adjustable by remote control
- Sensor: Infrared convergence-type proximity sensor



PFXE100CP

Optional Parts


OBPF107270288	4" Deck plate
OBPF508510067	0.35 gpm aerator
PFXEREMOTE	Remote control

Codes and Certifications



- Certified to ASME A112.18.1 / CSA B125.1
- cUPC/IAPMO listed
- ADA compliant


FLOW RATE VS PRESSURE



This graph applies to 0.5 gpm option only.

Specifications

PFXE100CP KERNA COMMERCIAL SENSOR LAVATORY FAUCET



For detailed warranty information, visit ferguson.com/proflo-faucet-warranty.